

Rasco Reinforcement Mesh

is an alkaline- and slide-resistant Reinforcement Mesh for the enforcement of **Rasco bitumen thick coatings** according to DIN 18195.

- · high stability
- · best application properties
- · alkaline-resistant glass fibre mesh
- · suitable for waterproofing according to DIN 18195



Areas of applicatoin

For the embedment and enforcement of **Rasco bituminous thick coatings** according to DIN 18195 parts 5 + 6. Suitable for the enforcement of **Rasco bitumen thick coatings** at critical, for example substrates at risk of cracking.

Technical Data	Colour	White
	Material	100% glass fibre
	Mesh size	approx. 3.5 mm x 3.5 mm
	Weight	≥ 150 g/m²
	Delivery unit	50 rm roll / 1.0 m width / 30 rolls per pallet
	Shelf life	24 months, if stored dry, protected from frost

General notes

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

Processing

- Rasco Reinforcement Mesh has to be cut to the relevant length and embedded fully and firmly using suitable tools into the first, fresh layer of Rasco Bitumen Thick Coating.
- The mesh is to be applied vertically with a minimum of 5 cm overlapping at the edges.
 The second layer of coating may be applied when the first layer may no longer be damaged during application.
- Rasco Reinforcement Mesh should be embedded in the centre of the completed, two-layered Rasco Bitumen Thick Coating and should not protrude out of the coating in any place.

Special notes

- Rasco Reinforcement Mesh is to be protected from sun, rain and frost before and during application until the Rasco Bitumen Thick Coating used is completely dry.
- · Information relating to **Rasco Bitumen Thick Coatings** and other product ranges can be found on our website http://www.rasco-bitumen.com).

Note: The information published in this sheet, in particular regarding the use and application of our products, is based on our experience and expertise. This may need to be adjusted, depending on the building itself, the purpose of use, and local working conditions. The product descriptions imply no basis for legal claims. Information provided by, and agreements with our employees, which are above and beyond the scope of this technical data sheet, require written

Issue: 01. This document has been issued for the first time in English. When this version is updated it will lose its validity.